## What is claimed is:

1

2

3

4

- 1 1. A machine-implemented method for managing access to data, the method comprising the 2 steps of: 3 detecting that a database command requires access to a particular combination of 4 information that is located in at least two tables; and 5 in response to the step of detecting, if the particular combination is a combination to 6 which access is limited, rewriting said database command by creating a modified 7 database command, based on the database command. 2. The method of claim 1, wherein the step of detecting causes an invocation of a policy that causes a generation of a condition expression; and wherein rewriting causes the modified database command to include the condition
- 1 3. The method of claim 2, wherein the generation of the condition expression is performed by referencing a policy function that returns the condition expression.
- 1 4. The method of claim 2, wherein the policy is not triggered by detecting that a database
  2 command requires access to a subset of tables of the at least two tables, wherein the subset of tables
- 3 includes at least one table.

expression.

- 1 5. The method of claim 2, wherein the detecting detects metadata includes one or more
- 2 parameters that indicate which tables and which columns of the tables form the particular
- 3 combination of information.

4

- 1 6. The method of claim 1, wherein the particular combination of information is a particular
- 2 combination of columns.
- 1 7. The method of claim 6, wherein the detecting includes detecting that metadata defines the
- 2 particular combination of columns as a combination of columns to which access is controlled.
- 1 8. The method of claim 1, further comprising the step of registering a policy function with a
- 2 policy, wherein the policy function returns a condition expression, and the modified database
- 3 command is based on the condition expression and the database command.
- 1 9. The method of claim 8, wherein the policy includes metadata identifying columns that are
- 2 included in the particular combination of information.
- 3 10. A machine-readable medium carrying one or more sequences of instructions, which when
- 4 executed by one or more processors, causes the one or more processors to perform a method
- 5 comprising the steps of:
- 6 detecting that a database command requires access to a particular combination of
- 7 information that is located in at least two tables; and
- 8 in response to the step of detecting, if the particular combination is a combination to which
- 9 access is limited, rewriting said database command by creating a modified database
- 10 command, based on the database command.

ORACLE CONFIDENTIAL

- 1 11. The machine readable medium of claim 10, wherein the step of detecting causes an
- 2 invocation of a policy that causes a generation of a condition expression; and
- 3 wherein rewriting causes the modified database command to include the condition
- 4 expression.
- 1 12. The machine readable medium of claim 11, wherein the generation of the condition
- 2 expression is performed by referencing a policy function that returns the condition expression.
- 1 13. The machine readable medium of claim 11, wherein the policy is not triggered by detecting
- 2 that a database command requires access to a subset of tables of the at least two tables, wherein the
- 3 subset of tables includes at least one table.
- 1 14. The machine readable medium of claim 11, wherein the detecting detects metadata includes
- 2 one or more parameters that indicate which tables and which columns of the tables form the
- 3 particular combination of information.
- 1 15. The machine readable medium of claim 10, wherein the particular combination of
- 2 information is a particular combination of columns.
- 1 16. The machine readable medium of claim 15, wherein the detecting includes detecting that
- 2 metadata defines the particular combination of columns as a combination of columns to which
- 3 access is controlled.

- 1 17. The machine readable medium of claim 10, wherein the method further comprises the step
- 2 of registering a policy function with a policy, wherein the policy function returns a condition
- 3 expression, and the modified database command is based on the condition expression and the
- 4 database command.
- 1 18. The machine readable medium of claim 17, wherein the policy includes metadata
- 2 identifying columns that are included in the particular combination of information.